

A standard linear barcode is positioned vertically on the right side of the page. It consists of vertical black bars of varying widths on a white background.

		Subclass
	Class	

ISSUE CLASSIFICATION

BEST AVAILABLE COPY

U.S. UTILITY Patent Application

O.I.P.E.
AD SCANNED JK3 Q.A. AB3

APPLICATION NO.	CONT/PRIOR.	CLASS	SUBCLASS	UNIT	ART UNIT	EXAMINER
09/837111		083	169		3724	<i>Drazen</i>
NAME OF INVENTOR				<i>Joseph H. Nethias</i>		
APPLICANTS	<i>Protek</i>					
TITLE	Band saw self cooling roller guide					
SEARCHED (initials):						
PTO-2040 12/99						

ISSUING CLASSIFICATION

TERMINAL DISCLAIMER	DRAWINGS			CLAIMS ALLOWED	
	Sheets Drwg.	Figs. Drwg.	Print Fig.	Total Claims	Print Claim for O.G.
<input type="checkbox"/> The term of this patent subsequent to _____ (date) has been disclaimed.				NOTICE OF ALLOWANCE MAILED	
<input type="checkbox"/> The term of this patent shall not extend beyond the expiration date of U.S Patent. No. _____				ISSUE FEE	
				Amount Due	Date Paid
<input type="checkbox"/> The terminal _____ months of this patent have been disclaimed.				ISSUE BATCH NUMBER	
				(Legal Instruments Examiner) (Date)	

The Information Possession Rule

Form PTO-438A FILER WITH: DISK (CDR) FICHE CD-ROM

Form PTO-438A
(Rev. 6/99)

FILED WITH: DISK (CRF) FICHE CD-ROM
(Attached in pocket on right inside flap)